

KX 250 X



**GET THE
OFF-ROAD
EDGE**

POWER

Type	4-stroke Single, DOHC, Liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 X 52.2 mm
Compression Ratio	14.1:1
Fuel System	Dfi® With 44 mm Keihin Throttle Body and Dual Injectors
Ignition System	Digital CDI
Transmission	5-speed, Return Shift, With Wet Multi-disc Manual Clutch
Final Drive	Chain

PERFORMANCE

Suspension:	Front	48mm Inverted Telescopic Coil-spring Fork with 23-way Compression Damping and 20-way Rebound Damping
	Rear	New Uni-trak® with Dual-range (2.25 Turns High Speed/21-way Low-speed) Compression Damping, 38-way Rebound Damping and Adjustable Preload
Wheel Travel:	Front	315 mm
	Rear	315 mm
Tyre:	Front	80/100-21
	Rear	110/100-18
Brake:	Front	Single Semi-floating 270 mm Braking® Petal Disc with Dual-piston Caliper
	Rear	Single 240 mm Braking® Petal Disc with Single-piston Caliper

DETAILS

Frame	Aluminum Perimeter
Caster (Rake Angle)	27.8°
Trail	122 mm
Overall Length	2,169 mm
Overall Width	820 mm
Overall Height	1,260 mm
Ground Clearance	330 mm
Seat Height	945 mm
Curb Weight	104 kg without fuel / 109 kg
Fuel Capacity	6.2 litres
Wheelbase	1,481 mm

* Specifications are subject to change without prior notice

** Pictures displayed are for illustration purposes only. Actual product may vary.

KX 250 X



Lime Green



Kawasaki
Technology



Scan For
Video Preview,
Key features
and More.



EMOS

199601019036 (391388-P) **Edaran Modenas Sdn. Bhd.**
EON Head Office Complex, Level 2, No. 2, Persiaran Kerjaya,
Taman Perindustrian Glenmarie, Seksyen U1, 40150 Shah Alam,
Selangor Darul Ehsan, Malaysia.

Kawasaki WhatsApp Care Line :
+6019 570 8135

Kawasaki Toll Free Line :
+1800 880 008